


## RomoCoat 34 PU Polyurethane Paint

**RomoCoat 34 PU Polyurethane Paint** is a **two-component acrylic aliphatic polyurethane finish** with high gloss, very good colour retention and strong resistance to water, chemicals, impact, abrasion and industrial corrosive atmospheres.

Designed as a high-gloss, light-fast, weather-resistant finish coat over suitable primers/intermediates on demanding industrial and OEM structures.

### Typical applications

- Finish coat on steel, aluminium, GRP (glass fibre reinforced polyester) and plywood where long-term gloss and colour retention are required.
- Ideal for exterior structural steel, machinery, tank exteriors, fabricated components, transport equipment and coastal/industrial atmospheres when applied over epoxy primers/intercoats.



### Product Data Sheet

Property	Details
<b>Mixing Ratio</b>	4 : 1 by volume
<b>Pot Life</b>	4-5 Hrs(30°C)
<b>Application Methods</b>	Airless Spray, Air Spray, Brush, Flow
<b>Nozzle Orifice</b>	0.017" – 0.019"
<b>Volume Solids</b>	Approx. 45%
<b>Finish</b>	High Glossy
<b>Colour</b>	Referred to the shade card
<b>Recommended DFT / Coat</b>	25–35 microns
<b>Theoretical Spreading Rate</b>	18.00-12.85 M2 /Ltr at above DFT
<b>Surface Dry</b>	~1 hour at 30°C
<b>Hard Dry</b>	16 hours
<b>Fully Cured</b>	7 days at 30°C
<b>Over coating Interval</b>	Min: 16 hours. Max: No 4 Weeks
<b>Flash Point</b>	Above 23°C

Trusted Industrial Paint Solutions Since 1987

**ROSALEE COLOURS PVT. LTD. - MONARCH CREATIONS GROUP**

**Mfg. Of Anti-Corrosive Primers, Epoxy – PU Paints, Rebar Protective Coat, Marine-Industrial Paints**

**Office:** 219, Narshi Natha Street, Mumbai-9 **Factory:** C-1, GIDC, Waghodia, Dist: Vadodara, Pin: 391760. India

Ph: 91-7077002037 | Mobile / WhatsApp: +91-9820334530 E-Mail: sales@rosaleepaints.com | Website: www.rosaleepaints.com



ISO 9001:2000  
Cert No: C77888



063

Property	Details
Thinner	P.U. Thinner

### Surface preparation & system

- Apply over suitable epoxy primer or epoxy intermediate coat; surface must be dry, clean and free from dirt and dust.
- Old primed/intermediate surfaces must be mechanically roughened (sanded) before PU application to ensure intercoat adhesion.

### Health, safety & storage

- Avoid inhalation of solvent vapour or paint mist and skin/eye contact; provide forced ventilation in confined or stagnant areas and use PPE as per local and national regulations.
- Store in a cool, dry, well-ventilated place, containers tightly closed and protected from direct sunlight and heat.

Trusted Industrial Paint Solutions Since 1987

**ROSALEE COLOURS PVT. LTD. - MONARCH CREATIONS GROUP**

Mfg. Of Anti-Corrosive Primers, Epoxy – PU Paints, Rebar Protective Coat, Marine-Industrial Paints

Office: 219, Narshi Natha Street, Mumbai-9 Factory: C-1, GIDC, Waghodia, Dist: Vadodara, Pin: 391760. India

Ph: 91-7077002037 | Mobile / WhatsApp: +91-9820334530 E-Mail: sales@rosaleepaints.com | Website: www.rosaleepaints.com



ISO 9001:2000  
Cert No: C77888



063